

PERUN T5



IP65



230 V
50 Hz



Ø 16
G 5

1-2,5 mm²





t 105 °C
t_a
45 °C

METAL
960 °C

1F

3F



Order code	Type	Light sources		Luminous efficiency %	Net weight kg	Dimensions mm				
		W				A	B	C	D	
with T5 electronic ballast – high efficiency range										
45510	PERUN 114 Anticor ET5	1x14	T5/G5	70	4,5	705	135	95	485	
45520	PERUN 128 Anticor ET5	1x28	T5/G5	69	5,5	1305	135	95	1095	
45530	PERUN 135 Anticor ET5	1x35	T5/G5	67	7,1	1605	135	95	1395	
45540	PERUN 214 Anticor ET5	2x14	T5/G5	66	5,5	705	200	95	485	
45550	PERUN 228 Anticor ET5	2x28	T5/G5	64	6,9	1305	200	95	1095	
45560	PERUN 235 Anticor ET5	2x35	T5/G5	63	9,6	1605	200	95	1395	
with T5 electronic ballast – high output range										
45515	PERUN 124 Anticor ET5	1x24	T5/G5	70	4,5	705	135	95	485	
45525	PERUN 154 Anticor ET5	1x54	T5/G5	69	5,5	1305	135	95	1095	
45535	PERUN 180 Anticor ET5	1x80	T5/G5	67	7,1	1605	135	95	1395	
45575	PERUN 149 Anticor ET5	1x49	T5/G5	67	7,1	1605	135	95	1395	
45545	PERUN 224 Anticor ET5	2x24	T5/G5	66	5,5	705	200	95	485	
45555	PERUN 254 Anticor ET5	2x54	T5/G5	64	6,9	1305	200	95	1095	
45565	PERUN 280 Anticor ET5	2x80	T5/G5	63	9,6	1605	200	95	1395	
45585	PERUN 249 Anticor ET5	2x49	T5/G5	63	9,6	1605	200	95	1395	

455x7 modification with dimmable electronic ballast T5 (ERT5=DIM)