

# PRIMA LED

INDUSTRIAL WATERPROOF, DUSTPROOF  
AND IMPACT RESISTANT  
fluorescent lighting fittings with LEDs



IP65



230 V  
50 Hz



LED

1-2,5 mm<sup>2</sup>



t<sub>a</sub>  
-20°C

PC  
850°C

#### Use:

Fluorescent PRIMA LED luminaires are suitable for illumination of areas with low ambient temperature. The lifetime of LEDs is not reduced with often switching.

#### Description:

The luminaires are equipped with high efficiency LED tubes (Ø 28 mm) with long service life.

The tubes have cooling aluminium profile and opal plastic cover.

Lampholder: GU10.

Order code	Type	Light sources	Luminous flux	Number of LEDs	Net weight	Dimensions	
		W	lm			A	D
with LEDs 6000 K daylight							
37313	PRIMA PC LED 110	1x10	735	128	0,7	662	350
37323	PRIMA PC LED 120	1x20	1534	256	1,5	1272	700
37333	PRIMA PC LED 125	1x25	1800	320	2,0	1572	940
37343	PRIMA PC LED 210	2x10	1470	256	1,3	662	350
37353	PRIMA PC LED 220	2x20	3068	512	2,4	1272	700
37363	PRIMA PC LED 225	2x25	3600	640	3,4	1572	940

373x1 modification LED 3000 K – warm white

373x2 modification LED 4000 K – cool white

374xx modification with stainless steel clips